



Customer: BAVARIA
 Sales manager: Mats Lindström
 Date created: 04-12-21
 Latest revision: 04-12-29
 Approved: 04-12-29 by NJ

Series production OK

General rig description

Conventional Fractional
 Keelstepped 2-spreader
 Tapered Sloop

Rig dimensions

Forestay height FH: 14 135 mm
 Main sail luff length P: 13 800 mm
 Boom height above deck BH: 1 110 mm
 Bury Q: 1 835 mm
 Main sail foot length E: 4 950 mm
 Main boom sheet pos S: 5 000 mm
 Spinnaker pole length SPL: 3 830 mm

Chainplates dist. from cl mast

	Lateral	Long	
Cap shrouds:	980	330 mm	(18,6°)
Aft lowers:	930	330 mm	
Deck above chainplates:	390 mm		
Deck above waterline:	1500 mm		

Hull and righting moment

Length: 10 650 mm
 Beam: 3 250 mm
 Draft: 2 000 mm
 Displacement: 5 700 Kg
 Ballast: 2 060 Kg
 Bulb/wing keel
 Equipped boat
 Heeling test RM: 31,1 kNm @30°

Spar sections

Mast: C211
 Boom: B143
 Spin. pole: S072

Furlex

Forestay: 207

Notes (6 lines)

Optional rodig sizes:
 V1,D1A:-12/7.1mm
 V2/D3,FS:-10/6.4mm
 D2: -6/5.0mm

